



Bounce Back[®]

floor finish restorer

Bounce Back is a floor finish restorer formulated with thermoplastic polymers for fast and easy finish touch-ups. Simply mop it on and then dry buff for a “just-waxed” shine!



Providing Quality Maintenance and Chemical Specialty Solutions with Unparalleled Customer Service



Spartan Chemical Company, Inc.
 1110 Spartan Drive
 Maumee, OH 43537
 1-800-537-8990
 www.spartanchemical.com

CONTINUOUS OPTIMAL FLOOR APPEARANCE:

Bounce Back offers excellent leveling characteristics increasing burnish response and providing a durable “wet look” gloss. Bounce Back will not streak, powder, or discolor the foundation floor finish.

REDUCES FLOOR MAINTENANCE COSTS:

Formulated to maintain a high gloss “wet look” between strippings, Bounce Back substantially reduces labor time spent stripping, resealing, and refinishing. Used on a regular basis, Bounce Back is an excellent preventative maintenance product resisting scuffs, scratches, and black heel marks.

ECONOMICAL:

Bounce Back is highly concentrated therefore, diluted according to directions. Diluted according to directions at 1:2 to 1:4, Bounce Back is far more economical than recoating.

PLEASANT, EASY, AND SAFE TO USE:

The Bounce Back formula incorporates a floral citrus fragrance providing a crisp, fresh scent, especially during the burnishing process. Easy to use, simply mop on Bounce Back, allow to dry and dry buff.

DIRECTIONS FOR USE:

Some individuals may be sensitive to ingredients in this product. Before using, read product label and MSD sheet. Wet floors may be slippery. Prevent pedestrian traffic with signs or barricades.

1. Make certain the floor is clean and dry.
2. Pour water in the bucket first and then add Bounce Back. For best results, mix 2 gallons of water with 1 gallon of Bounce Back. For optimum economy, experiment with dilutions. One gallon of Bounce Back can be mixed with up to 4 gallons of water.
3. Wet a clean cotton, rayon, or wax and seal mop with the diluted Bounce Back solution. Wring out the mop until it no longer drips and apply Bounce Back in a figure eight motion.
4. Allow 15 to 30 minutes drying time and buff immediately. Experiment with pads for best results.

Use Spartan’s Damp Mop daily and Bounce Back finish restorer at least once a week to insure continuous optimal floor appearance.

Be sure to read all Directions, Precautionary and First Aid Statements on product labels before use of this or any Spartan product. If questions remain, consult your employer or a physician. Material Safety Data Sheets for all Spartan products are available from your authorized Spartan distributor or by visiting www.spartanchemical.com.

SPECIFICATIONS:

Specific Gravity – 1.01 @ 24°C/75°F
 pH (Concentrate) - 8.1 – 8.6
 Non-volatile Solids (Concentrate) - 17 – 18%
 Stability
 a. Storage @ 24°C/75°F - One year minimum
 b. Accelerated @ 52°C/125°F - 30 days minimum
 c. Freeze/Thaw - Can withstand three cycles



Distributed by:

| PACKAGING | |
|-----------|-----------------------|
| 433065 | 330-gallon tote |
| 433055 | 55-gallon drum |
| 433030 | 30-gallon drum |
| 433015 | 15-gallon drum |
| 433005 | 5-gallon pail |
| 433004 | 1-gallon (4 per case) |



Label copy is provided in English, Spanish, and French. Secondary labels are also available.

GUARANTEE: Spartan’s modern manufacturing and laboratory control insure uniform quality. If dissatisfied with performance of product, any unused portion may be returned for credit within one year of the date of manufacture. Use product as directed and read all precautionary statements.



Product Available Worldwide. For institutional and industrial use only.

© SCC 5/11 L4330